



NOTES

- ① SLOTTED CROSS GUTTER SHALL BE USED ONLY WHEN APPROVED BY THE CITY ENGINEER.
- ② TYPE "B" GUTTER WIDTHS AT B.C.'S AND E.C.'S SHALL BE PER STANDARD DRAWING NO. 1201, OR MATCH EXISTING.
- ③ SEE STANDARD DRAWING NO. 1106 FOR CURB RETURN RADII AND 1209 FOR PROPERTY LINE CORNER CUT-BACK.
- ④ CONCRETE SHALL BE CLASS 520-C-2500 PER SECTION 201 OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, CURED WITH TYPE 1-D CURING COMPOUND.
- ⑤ ALTERNATE A SHALL BE USED WHEN ADJACENT TO A 5' STRIPED CLASS II BIKE LANE.
- ⑥ CAB SHALL BE PLACED BENEATH SPANDREL.



| | | |
|---------------------------------------|--------------------|------------|
| APPROVED BY: | <i>[Signature]</i> | 8-13-24 |
| | | DATE |
| KHOI DO, CITY ENGINEER | | RCE: 62809 |
| RECOMMENDED BY: | <i>[Signature]</i> | 8/12/24 |
| | | DATE |
| BRYAN LIRLEY, ASSISTANT CITY ENGINEER | | RCE: 70990 |

CITY OF ONTARIO

CROSS-GUTTER

STANDARD DRAWING NUMBER

1208