



LEGENDS

- ⊙ INDICATES MONUMENTS SET AS 2"X24" IRON PIPE WITH BRASS NAIL (OR SIMILAR ALLOY) AND TAG STAMPED WITH L.S. OR R.C.E. NUMBER (A 2-1/2" BRASS DISK STAMPED WITH RANGE, TOWNSHIP AND SECTIONS WHEN SET AT QUARTER OR SECTION CORNERS). SEE STANDARD DRAWING 6103.
- INDICATES MONUMENTS SET AS 1"X18" IRON PIPE, WITH BRASS NAIL (OR SIMILAR ALLOY) AND TAG STAMPED WITH L.S. OR R.C.E. NUMBER, UNLESS OTHERWISE NOTED. BRASS NAIL (OR SIMILAR ALLOY) AND TAG MAY BE SET IN TOP OF CURB ON FRONT PROJECTION OF ALL SIDE LOTS IN LIEU OF 1"X18" IRON PIPES. SEE STANDARD DRAWING 6103.
- ⊞ INDICATES SET MONUMENT WELL, SEE STANDARD DRAWING 6102.
- SOLID SYMBOL INDICATES MONUMENT FOUND AS NOTED.

NOTES

1. REFER TO STANDARD DRAWINGS 6107 FOR SUBDIVISION MONUMENT REQUIREMENTS.
2. REFER TO STANDARD DRAWINGS 6101, 6108, 6109, AND 6110 FOR STREET TIE REQUIREMENTS.
3. UNIQUE FILLED SYMBOLS ARE TO BE USED FOR ALL FOUND MONUMENTS REFERENCED.
4. WHEN A CENTERLINE POINT LANDS ON OR NEAR A MANHOLE, 4-MAG SPIKE (MINIMUM 4-1/2") AND WASHER CROSS-TIES ARE TO BE SET.
5. A BRASS NAIL AND 3/4" BRASS TAG STAMPED WITH L.S. OR R.C.E. NUMBER MAY BE SET IN LIEU OF AN IRON PIPE AT LOT CORNERS OR IF A CORNER LANDS ON A WALL OR ITS FOUNDATION.



APPROVED BY:				
		5-22-24		
KHOI DO, CITY ENGINEER		62809	RCE	DATE
RECOMMENDED:				
		70990 5/22/24		
BRYAN CURLEY, ASSISTANT CITY ENGINEER		RCE	DATE	
REV	DESCRIPTION	BY	APP'D	DATE

CITY OF ONTARIO

SUBDIVISION
MONUMENT STANDARD
PLAN

STANDARD
DRAWING
NUMBER

6106