


				CURVE 1			CURVE 2						CURVE 3								
				Δ ₁	CURB LINE			Δ ₂	CURB LINE			PROPERTY LINE			Δ ₃	CURB LINE			PROPERTY LINE		
W	W/2	P	PK		R	L	T		R	L	T	R	L	T		R	L	T	R	L	T
60'	30'	18'	12'	VARIES	25'	VARIES	VARIES	9'43"36"	50'	8.49'	4.25'	38'	6.45'	3.23'	Δ ₁ +2(Δ ₂)	58'	VARIES	VARIES	70'	VARIES	VARIES
60'	30'	20'	10'	VARIES	25'	VARIES	VARIES	12'6"24"	50'	10.57'	5.30'	40'	8.45'	4.24'	Δ ₁ +2(Δ ₂)	63'	VARIES	VARIES	73'	VARIES	VARIES
66'	33'	20'	13'	VARIES	25'	VARIES	VARIES	13'33"2"	50'	11.83'	5.94'	37'	8.75'	4.40'	Δ ₁ +2(Δ ₂)	68'	VARIES	VARIES	81'	VARIES	VARIES
66'	33'	24'	9'	VARIES	25'	VARIES	VARIES	8'47"15"	50'	7.67'	3.84'	41'	6.29'	3.15'	Δ ₁ +2(Δ ₂)	66'	VARIES	VARIES	75'	VARIES	VARIES

NOTES

1. MINIMUM FLOWLINE GRADE SHALL BE 0.6%.
2. CURB CONSTRUCTION SHALL BE PER STANDARD DRAWING NO. 1201.
3. SIDEWALK CONSTRUCTION SHALL BE PER STANDARD DRAWING NO. 1209, OR 1210 AS DETERMINED BY THE CITY ENGINEER.



APPROVED BY:				CITY OF ONTARIO			
<i>[Signature]</i>				KNUCKLE			
LOUIS ABI-YOUNES, CITY ENGINEER				STANDARD DRAWING NUMBER			
RCE DATE				1104			
RECOMMENDED:							
<i>[Signature]</i>							
KHOI DO, ASSISTANT CITY ENGINEER							
RCE DATE							
62809 2/22/16							
REV							
DESCRIPTION							
BY							
APP'D							
DATE							