

SECTION A-A

CM = CURB MEDIAN

CF = CURB FACE

SW = SIDEWALK R/W = RIGHT OF WAY

DW = DOMESTIC WATER

G = GAS

L = STREET LIGHTING

RW = RECLAIMED WATER

S = SEWER

SD = STORM DRAIN

T = TELEPHONE/FIBER OPTIC

TV = CABLE TELEVISION


E = ELECTRICAL

SI = SIGNAL INTERCONNECT

FO = CITY FIBER OPTIC /W PULL ROPE

NOTES

- 1. PROVIDE 1' MIN. CLEARANCE AT UTILITY CROSSINGS
- 2. BETWEEN CURBS, COVER FOR LATERALS SHALL NOT BE LESS THAN 30" BELOW ROADWAY SURFACE.
- MIN. SEPARATION BETWEEN WATER AND SEWER SHALL BE PER CITY STANDARD DRAWING NUMBER 4001.
- 4. VARIATIONS FROM STANDARD WILL REQUIRE PRIOR APPROVAL FROM CITY ENGINEER.
- 5. SEE STANDARD DRAWING 5014 FOR CURB RETURN AREA CLEAR ZONES.
- 6. A SINGLE, 2' WIDE MAXIMUM COMMON DRY UTILITY DUCT BANK (TO INCLUDE ELECTRIC, TELELPHONE, GAS AND FIBER OPTICS) WILL BE ALLOWED. MINIMUM COVER WILL BE 42" TO CROSS THE CLEAR ZONE PER CITY STANDARD DRAWING NUMBER 5203 AND SHALL NOT BE LOCATED MORE THAN 1-FOOT OFF THE RIGHT-OF-WAY LINE.
- 7. PROVIDE 4' MINIMUM WALL TO WALL CLEARANCE FOR ALL UTILITIES.
- 8. INSTALL (1) PULL ROPE WITHIN THE CITY FIBER OPTIC CONDUIT TO VERIFY CONTINUITY.



CITY OF ONTARIO

UTILITY LOCATIONS FOR STANDARD STREET SECTIONS STANDARD DRAWING NUMBER

1302